



Raycap

Strikesorb Technology
for the Protection
of Wind Turbines

Strikesorb® Lightning Protection Solutions for Wind Turbine Applications

Requirements for Surge Protective Devices (SPD) to be used in wind turbine applications

- Withstand lightning currents**
 The SPD will be exposed to locations where it must withstand lightning currents following a 10/350 waveform.
- Long lifetime**
 The SPD should have a lifetime longer than the expected 20-year lifetime of a wind turbine. The SPD should never fail, even in harsh lightning environments, where exposure to direct lightning is much higher than average.
- Continuous and efficient protection of the equipment**
 Under any condition, the SPD should always protect the equipment. This means that it should not disconnect itself from the power lines to self-protect, leaving the equipment unprotected. Further, it should provide a very low protection level that protects the equipment efficiently while maintaining it in good condition over its expected lifetime.
- Optimized solutions available**
 The SPD line should be optimized in terms of available size and cost, according to the requirements of the installation.
- Maintenance-free**
 In wind turbine applications the SPD should not have to be inspected frequently, as this requirement will result in increased maintenance costs.
- Compliant to global regulations**
 As wind turbines can be supplied to any country around the world, the SPDs integrated inside of them should comply with and be certified according to all relevant local and international standards.



Strikesorb Modules

Information in this chart is subject to change at any time without notice.

*690V per IEC 61643-11
 **400V per IEC 61643-11
 ***480V per IEC 61643-11

Key benefits of Raycap's unique and enhanced Strikesorb surge protection technology

- Maximum lightning current of up to 25kA 10/350**
 Strikesorb is available in three versions with an impulse discharge current rating (I_{imp}) from 5kA up to 25kA.
 - More than 20 years of lifetime and an excellent product warranty**
 Strikesorb is a proven technology that has been in existence for 20-plus years, having more than 10 years of use in the wind generation industry. More than 20 million modules have been installed in mission-critical applications, with a failure rate of practically zero. Strikesorb modules have a 10 year warranty.
 - Direct installation on power lines enables uninterrupted and optimized equipment protection**
 The most important aspect of the Strikesorb technology is its ability to safely withstand significant amounts of energy before and after its end of life, as the failure mode of the device is a short circuit of very low impedance. Therefore, it can sustain very high short circuit currents until the upstream fuse or circuit breaker trips. The high short circuit current rating and connecting terminals of Strikesorb enable its direct installation onto the power lines. This results in low residual voltage to the equipment with no requirement for long connecting cables, series fuses or circuit breakers, which may trip and leave the load unprotected.
- Strikesorb will never leave the equipment unprotected. In case of a catastrophic event, either a lightning current that exceeds the Strikesorb specifications or a prolonged temporary overvoltage (TOV) condition, the Strikesorb module will not disconnect from the power system.

- Very low let-through voltage**
 Strikesorb offers by design the lowest voltage protection level among different technologies. Its design features in combination with an in-line installation result in very low protection levels which in turn protects sensitive and mission-critical equipment exposed to harsh environments.
- Several sizes cover all locations**
 All possible locations inside the wind turbine can be protected by the most efficiently-sized SPD. The size of SPD needed depends on the lightning current withstand capacity and the short circuit current rating of the modules. This allows optimized panel designs and well engineered solutions with in-line connections to power lines.
- Maintenance free operation**
 Strikesorb modules do not rely on internal disconnectors or dedicated low rated fuses, so they do not require a maintenance plan.
- Dual certification (UL/IEC)**
 Strikesorb has UL (per UL 1449) and VDE (per IEC 61643-11) markings that allow the panels in which it is integrated to be compliant to all relevant US and international standards. When integrating Strikesorb SPDs into products, users never need to worry about the compliance of their products in any country across the world.



Strikesorb Electrical Specifications†		30-A 30-B 30-C 30-D				40-V1 40-A 40-B 40-C 40-D 40-E 40-F 40-G							80-A 80-B 80-C 80-D 80-E 80-F							
Strikesorb Modules		Type 2 Component Assembly				Type 2 Component Assembly							Type 2 Component Assembly							
Surge Protective Device (SPD) Type		Class I+II				Class I							Class I							
per UL 1449 5 th Edition		Class per IEC 61643-11				Class I							Class I							
Nominal Operating AC Voltage [U _n]		120V	240V	277V	480V**	60V	120V	240V	277V	480V**	480V	600V	1000V	120V	240V	277V	480V**	480V	600V	
Maximum Continuous Operating AC Voltage [U _c]		150V	275V	350V	550V***	75V	150V	300V	350V	550V***	600V	750V*	1200V	150V	300V	350V	550V***	600V	750V*	
Nominal Discharge Current [I _n]	per UL 1449 5 th Edition	20 kA 8/20µs				20 kA 8/20µs							20 kA 8/20µs							
Maximum Surge Current Capacity [I _{max}]	per NEMA LS-1	60 kA 8/20µs				140 kA 8/20µs							200 kA 8/20µs							
Impulse Discharge Current [I _{imp}]	per IEC 61643-11	5kA 10/350µs		7.5 kA 10/350µs		12.5 kA 10/350µs							25 kA 10/350µs							
Over Current Protection [I _{SCCR}]	per IEC 61643-11	50kA (with 630A CB)				50kA (with 1600A CB)							50kA (with 1600A CB)							
SCCR (Over current protection)	per UL 1449 5 th Edition	42kA (800A CB) 100kA (600A Fuse)				200kA (4000A Fuse)		200kA (4000A Fuse)		100kA (800A CB)		100kA (600A Fuse)			200kA (4000A Fuse) 65kA (800A CB)					
Voltage Protection Rating (VPR)	per UL 1449 5 th Edition	700V	1200V	1500V	1800V	400V	600V	1200V	1200V	1500V	2000V	2500V	4000V	600V	900V	1200V	1200V	1800V	2000V	
Voltage Protection Level [U _p]	per IEC 61643-11	700V	1200V	1600V	2200V	300V	600V	1200V	1300V	1800V	2300V	2800V	4400V	600V	1000V	1200V	1600V	1900V	2400V	

Raycap Worldwide Locations



Raycap Inc.
806 South Clearwater Loop
Post Falls, ID 83854
United States of America

7555-A Palmetto Commerce Pkwy
North Charleston, SC 29420
United States of America

46 Sellers Street
Kearny, NJ 07032
United States of America

Raycap GmbH
Parkring 11
85748 Garching Munich
Germany

Raycap S.A.
Telou & Petroutsou 14
15124 Maroussi Athens
Greece

Raycap S.A. Manufacturing
Industrial Area of Drama
66100 Drama
Greece

Raycap d.o.o.
Pod hrasti 7
Poslovna cona Žeje pri Komendi
1218 Komenda
Slovenia

Raycap Cyprus Ltd.
46 Lefkosias Street
Industrial Area of Dali
2540 Nicosia
Cyprus

Raycap SAS
84 rue Charles Michels
Building B
93200 Saint-Denis
France

Raycap Corporation SRL
102, Barbu Vacarescu
entrance D, 4th floor, D22
020283, Bucharest
Romania

Raycap (Suzhou) Co. Ltd.
Block B, Phase II
of New Sea Union
No. 58 Heshun Road
SIP, Suzhou 215122
Jiangsu Province
China



Raycap

raycap.com • info@raycap.com

Raycap and Strikesorb are registered trademarks.
© 2024 Raycap All rights reserved.
G02-01-187 240404